



[radwag.com](http://radwag.com)



#### XA 200.5Y.KO Mass Comparator

More information on the website  
[radwag.com/en/info,w1,RUB](http://radwag.com/en/info,w1,RUB)



XA 200.5Y.KO Mass Comparator

The drawings, photos and graphics used are for illustrative purposes only.

## Functions

- Automatic sliding door

# Datasheet

	<b>XA 200.5Y.KO Mass Comparator</b>
<b>Metrological parameters</b>	
<b>E1 Calibration Range</b>	200 g
<b>E2 Calibration Range</b>	50 g ÷ 200 g
<b>F1 Calibration Range</b>	50 mg ÷ 200 g
<b>F2 Calibration Range</b>	1 mg ÷ 200 g
<b>M1 Calibration Range</b>	1 mg ÷ 200 g
<b>M2 Calibration Range</b>	1 mg ÷ 200 g
<b>Maximum capacity [Max]</b>	210 g
<b>Readability [d]</b>	0,01 mg
<b>Standard repeatability [5% Max]</b>	0,005 mg
<b>Standard repeatability [Max]</b>	0,025 mg
<b>Permissible repeatability</b>	0,05 mg
<b>Eccentricity (tested load)</b>	1d / 1 mm
<b>Electric compensation range</b>	0 ÷ 210 g
<b>Stabilization time</b>	5 s
<b>Adjustment</b>	internal (automatic)
<b>Physical parameters</b>	
<b>Display</b>	10" graphic colour touchscreen
<b>Weighing pan dimensions</b>	ø90 mm
<b>Weighing device dimensions</b>	564x253x300 mm
<b>Controlling device dimensions</b>	249x170x72 mm
<b>Packaging dimensions</b>	765x515x545 mm
<b>Net weight</b>	15,7 kg
<b>Gross weight</b>	20,1 kg
<b>Communication interface</b>	
<b>Communication interface</b>	2xUSB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Environmental conditions</b>	
<b>Operating temperature</b>	+15 ÷ +35 °C
<b>Operating temperature change rate</b>	±1°C/12h
<b>Relative humidity</b>	40% ÷ 70%
<b>Relative humidity change rate</b>	±5%/4h

Repeatability is expressed as a standard deviation determined for 6 ABBA cycles. Standard deviation is experimentally determined under ambient conditions for calibration of F2 class mass standards specified in OIML R111 (Table C.1.) document.

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



## Accessories

RFID Tags  
Antivibration Tables  
Additional modules  
Protective cover for balances  
Barcode scanners  
RS 232, RS 485 cables  
Label Printers

THBR 2.0 System - Ambient Conditions Monitoring  
Anti-Draft Chamber for XA 4Y and XA 5Y Balances  
Receipt Printer  
Fingerprint Reader  
RS 232, RS 485 cables  
RS 232 cables (scale - printer)

# Software

RAD-KEY  
RMCS System

RMCS Lite

## Device dimensions

XA 200.5Y.KO Mass Comparator 